Determining the Sula block kinematics in the triple junction area in Indonesia by GPS

Andrea Walpersdorf [1], and Christophe Vigny

Ecole Normale Supérieure, Laboratoire de Géologie, Paris, France

P. Manurung, C. Subarya and S. Sutisna

BAKOSURTANAL, Cibinong, Indonesia

Abstract. The point of convergence of the Eurasian, Philippine, and Australian Plates, is situated adjacent to the island of Sulawesi, Indonesia. The relative plate velocities are estimated by NUVEL1 to be 7 to 9 cm/yr. The complex tectonic mechanism of the triple junction has been studied over a two year period in the course of the GEODYSSEA South-East Asian Project. The GPS investigations concentrate on both, measurements of the Sulawesi (Eastern Indonesia) part of the inter-regional GEODYSSEA network, and on a local sub-network on Sulawesi. Motions derived using data from the sub-network confirm what the results of the inter-regional GEODYSSEA network have suggested: that current deformation is high and includes distinct deformation domains in the study area on Sulawesi. The tectonic mechanism of the triple junction has been analyzed using a rigid micro-block model. The triple junction area can be best interpreted as headland of the Australian Plate deflected by its collision with the Philippine Plate, hereby identifying the driving forces of the current deformations. The northern part is dominated by the Sula domain displaying clockwise rotation. To the South, it is connected to the Australian Plate by an ensemble of micro-blocks in counter clockwise rotation. In addition to the above stated, our tectonic model permits the determination of the local influence of two large earthquakes (on 1 January 1996 with M=7.8 and 22 July 1996 with M=7.0) on the motion of the Tomini station (North Sulawesi). Intensified observations and densification of the GPS network are planned in order to study the behaviour of the Palu-Koro Fault, the main fault on the Sula block's western limit.

Key words: Tectonics, GPS, Sulawesi, Triple junction, Indonesia

1. Introduction

The GEODYSSEA network in South East Asia covers the area adjoining the conjunction of the Eurasian, the Philippine and the Australian plates. The rigid plate kinematic model NUVEL1-A [*DeMets et al.*, 1994] predicts very high relative velocities of 7.5 to 9.0 cm/yr between the major plates, and a derived apparent triple junction in Eastern Indonesia (Fig. 1).

About 40 GEODYSSEA GPS stations have been installed and measured during two observation campaigns in December 1994 and April 1996, as a part of the international project between the European Union and the ASEAN countries: Indonesia, Malaysia, Singapore, the Philippines, Thailand, Vietnam and Brunei [*Wilson and Rais*, 1998]. Comparing the solutions produced by 4 independent data processing centres, *Angermann et al.* [1998] showed that the observations are precise to about 5 mm/yr on 1000 km baselines. In this paper those results from the GPS observations are presented that cover what is known as the most highly deforming area of the GEODYSSEA network: the triple junction region between Sulawesi and the Moluccas in Eastern Indonesia (Fig. 1).

According to NUVEL1A, the triple junction is of a Trench-Trench-(transform) Fault (TTF) type, with the Australian and the Philippine plate subducted underneath the Eurasian plate, and the Australian-Philippine boundary displaying left lateral strike slip faulting (with a small reverse component). A closer look at the tectonic features in the triple junction area (Fig. 1) shows that its mechanism is more complicated than the intersection of three simplified plate boundaries described above may imply.

In the following, the tectonic mechanism is analyzed by a model in terms of rigid block rotations, based on the observed velocities. The model uses those rotation poles that fit best to the observed tectonic configuration and kinematics, and evaluates the rates of rigid rotation. By examining the residuals between model and measured velocities, actively deforming areas are identified in detail. Furthermore, the model permits the estimation of the continuous secular motion of a station affected by earthquakes, hereby separating the co-seismic displacements which help to constrain the earthquake mechanisms.

2. Tectonic settings

The triple junction area between the island of Sulawesi and the Moluccas in Eastern Indonesia shows a very complex tectonic scenario. Fig. 1 displays a compilation of tectonic features which are acknowledged to be active, based on *Rangin et al.* [1998], *Rangin* [1989], *Hall et al.* [1991], *Silver et al.* [1983] and *Moore and Silver* [1983]. Instead of a simple intersection of three plate boundaries, one sees, for example, that the collision of the Philippine and the Eurasian plate is absorbed by the double subduction zone in the Molucca Sea (features 4 and 5 in Fig. 1). The Philippine and the Australian plates are separated by the Sula Sorong fault (feature 6) and the subduction zone north of Seram (7). The Sula block collides north-west of Sulawesi with the Eurasian plate under the constraints of the Australian and Philippine plate motions. This

[1] Now at Delft Institute for Earth-Oriented Space Research, Delft University of Technology, The Netherlands.